

Custom Module USB Charger

Custom Module for DIGIMIC lean⁺

Article No.: 62.1105



Description

With the new USB double charger (5V / 2,4A) in custom module size, the charging of end devices is a child's play: The universal and flexible solution is particularly suitable for retrofitting of DIGIMIC lean⁺ conference delegate's units with custom module mounting, for which no charging variant has been available so far.

The USB chargers are powered by the Wieland GST18i3 device connector. By default the chargers are supplied with protection against overcharging, over-voltage, short circuit and overheating.

Advantages of DIGIMIC lean⁺ custom modules:

- Flexibly interchangeable modules
- For data, video and audio connections
- Can be used in all conference delegate units with custom module technology
- Integration with the switch ranges of leading manufacturers
- Easy to connect via socket/socket or screw terminals

Features

Electrical parameters

- Rated current / rated voltage 250V~
- Output: 5 V DC / max. 2,4 A
- Frequency 50/60 Hz
- Charging current 2,4A max.
- Internal consumption <0,1W

Product attributes

- Front: 2 x USB-A connector
- Rear: GST18i3 plug with approx. 0.2 m cable
- Charging Devices:
Apple Devices Fast Charging, Samsung Galaxy Tab Devices Fast Charging, BC1.2 Charging Specification

Environmental conditions

- Operating temperature 0°- 35°C
- Storage temperature -25°- 60°C

Certified according to

IEC 62368-1:2014
IEC 60065:2014
IEC 60950-1:2005

System requirements

Conference delegate units DIGIMIC lean⁺ with custom module functionality.

Their construction offers you simple and flexible installation in conference systems. The versatility of custom modules makes DIGIMIC lean⁺ with custom modules even more flexible.

With the easy-to-swap modules you can create delegate units to meet the individual data, video and audio connection requirements of your customers quickly and simply.